

VULCAN-VULCAP MPB Tire Section Repair Mold

| <u>PART#</u> | <u>DESCRIPTION</u> | SHIP WT. | | <u>TIRE RANGE</u> |
|-----------------------------------|--|------------|-----------|--|
| | | <u>lbs</u> | <u>kg</u> | |
| 902000 | Passenger Section Repair Mold, 110 or 220V, Single Phase includes Main Airbag, Outside Heatpad, 2 Bead Filler Pads, 1 Side Filler Pad, Air Differential Control Panel and MO Inflatable Mandrel Package (consisting of Mandrel, Adaptor and "AAA" Inside Heatpad") | 150 | 68.2 | Passenger-145/70R10 24.5/70 24.5/70R15 Industrial 6.00x9-7.00x12 Light Truck - 6.50x16 to 7.50 x 17 |
| 903000 | MPB Special for High Performance Low Profile Tires up to rim diameter of 20" | | | NOTE: For complete tire range, M1 package as an extra is required. |
| CRATED DIMENSION: 24" x 24" x 30" | | | | |

MPB REPLACEMENT PARTS AND ACCESSORIES

| MO INFLATABLE MANDREL PACKAGE | | | | |
|--|--|---|-----|--|
| 920000 | Inflatable Mandrel | 5 | 2.3 | Passenger & Industrial 9"-12" Rim dia. |
| 919800 | Mandrel Adaptor | 8 | 3.6 | |
| 904800 | "AAA" Inside Heatpad | 4 | 1.8 | |
| M1 INFLATABLE MANDREL PACKAGE | | | | |
| 919600 | Inflatable Mandrel | 8 | 3.6 | Passenger Series 78 & 75, (13"-15" Rim dia.) Light Truck 6.50-7.50 (15"-16" Rim dia.) |
| 919800 | Mandrel Adaptor | 8 | 3.6 | |
| 904800 | "AAA" Inside Heatpad - OR - | 4 | 1.8 | |
| 903700 | "AA" Inside Heatpad | 5 | 2.3 | |
| (Use "AA" Heatpad for larger tires only) | | | | |
| LOW PROFILE AIRBAG KIT | | | | |
| 920100 | Use with any Inflatable Mandrel Package for extra pressure on Shoulder and Sidewall area | 5 | 2.3 | |